



SETTING STANDARDS IN HAULING™



MODEL 8TSL
 Aluminum Modular Body
 Enclosed Contour Wheel Fenders
 Dual Rear Electronic Controls
 Wireless Remote
 Dual 8,000 lb. Winches
 Dual Hydraulic Stiff-Legs



WRECKER • 8-TON-INTEGRATED SELF-LOADER

8-Ton Wrecker: 8TSL



SELF-LOADER WHEEL-LIFT PACKAGE



Rear Electronic Switch Controls & Wireless Remote

- OPTIONS*:**
- Various Winches & Cables
 - Wrecker Special Light Bar
 - Custom Paint
 - Rear View Camera
 - 24" Tunnel Tool Box
 - Engine Driven Clutch Pump

SPECIFICATIONS**

RECOVERY BOOM

Boom rating at boom swivel
 Maximum Angle
 Lift height from ground to hook at max. elevation
 Reach past tail-board minimum elevation
 Reach past tail-board maximum elevation

Specs	Retracted	Extended
	16,000 lbs.	8,000 lbs.
	35°	
	105-7/8"	134-1/2"
		58-3/4"
		30-1/2"

UNDER-LIFT

Lift Capacity at Full Extension
 Range of Tilt
 Distance from Bumper to Center Line of Lift Arm
 Tow Rating

Specs	Retracted	Extended
		4,000 lbs.
	-22° down to 71° up	
	51"	80-5/8"
	7,500 lbs.	

WINCH & CABLES

Winch Rating: 1st Layer of each drum/winch
 Cable diameter and length each drum

Specs
8,000 lbs.
3/8" x 100'

CHASSIS RECOMMENDATIONS

Cab to axle:
 Cab to axle: 24" tunnel box
 Minimum GVWR
 Maximum GVWR
 Minimum frame RBM

Specs
60"
84"
15,000 lbs.
26,000 lbs.
280,000 in-lbs.

**Ratings are based on structural factors only, not chassis capacity. Prices & Product Specifications subject to change without notice. Specifications may vary depending on the chassis selected. Optional equipment may be shown in photographs and may not be part of the standard package. See dancoproducts.com for a more complete list of specs.

*Optional upgrade prices not included in standard pricing.



Hydraulic Stiff-Legs



DISTRIBUTED BY:



Holly Newlin
 holly@dancoproducts.com
 411 S. Cedar Lane
 Greencastle, PA 17225
 800-453-2626 • 717-597-7185

dancoproducts.com
 MADE IN THE USA • GREENCASTLE, PA

